




code: 246425 EAN: 5901583246425

LED line® downlight aluminium 360° adjustable white





Product vertically and horizontally adjustable.



MATT

appearance.

Manufacturer issues a 5-year warranty for this product.

Product coated with a matt paint finish which gives aesthetic

Mounting hole diameter


into any direction.

Parameter	Value
Maximum suitable lamp power	35
IP protection rating	20
Warranty (years)	5
Colour	white
Fixture's diameter	130
Lamp's diameter	50
Material (housing)	DIE-CAST alu
X-axis angle regulation	360
Y-axis angle regulation	75
Type of surface suitable for installation	F


Distance from illuminated surface0.5Installation methodrecessedMounting hole diameter110 mmFor indoor and outdoor useYESIEC protection classIIIFull box quantity24 pcHeight80 mmProduct weight with packaging300 gMaster carton weight (kg)7,2	Parameter	Value
Mounting hole diameter110 mmFor indoor and outdoor useYESIEC protection classIIIFull box quantity24 pcHeight80 mmProduct weight with packaging300 g	Distance from illuminated surface	0.5
For indoor and outdoor useYESIEC protection classIIIFull box quantity24 pcHeight80 mmProduct weight with packaging300 g	Installation method	recessed
IEC protection classIIIFull box quantity24 pcHeight80 mmProduct weight with packaging300 g	Mounting hole diameter	110 mm
Full box quantity24 pcHeight80 mmProduct weight with packaging300 g	For indoor and outdoor use	YES
Height 80 mm Product weight with packaging 300 g	IEC protection class	III
Product weight with packaging 300 g	Full box quantity	24 pc
	Height	80 mm
Master carton weight (kg) 7,2	Product weight with packaging	300 g
	Master carton weight (kg)	7,2



Single packaging



Bulk packaging



Europallet

