

LED line LITE



Code: 203921

EAN: 5905378203921

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 60x60cm white Surface-
mounted/Recessed LITE**



The Backlit Panel 2in1 40W 4000K 4000LM with dimensions 595x595 mm is an innovative LED fixture by LED line LITE, distinguished by high quality of workmanship and efficiency. Thanks to the use of SMD LED diodes, it offers excellent luminous efficiency at the level of 100 lm/W and a stable luminous flux of 4000 lm. The housing allows for easy installation both surface-mounted and recessed in Armstrong ceiling systems.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	>=0,95
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	38 mm
Material (housing)	Metal
Material (cover)	Polystyrene


LED line LITE

Code: 203921


EAN: 5905378203921

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 60x60cm white Surface-
mounted/Recessed LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Width	600 mm
Height	45 mm
Length	610 mm
Weight	1,5 kg

Bulk packaging

Quantity	6
Width	300 mm
Height	625 mm
Length	625 mm
Volume	0,117 m ³
Weight	9,2 kg

Europallet

Quantity	72
Height	1860 mm
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	140 kg

LED line LITE

Code: 203921

EAN: 5905378203921

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 60x60cm white Surface-
mounted/Recessed LITE**

Example application