

LED line LITE

Code: 477637

EAN: 5907777477637

LED line LITE TRI-PROOF 90W 4000K
1550mm



product_card.label_technical_data

Parameter	Value
Luminous efficacy	120 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	10800 lm
Colour consistency in McAdam ellipses	≤6
Standby power	0
IP protection rating	IP65
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
Colour	White
The lumen maintenance factor	96 %
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	Polycarbonate

Parameter	Value
LED type	2835
LED quantity	240
Lifespan	35000
Power Factor	0,9
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	08
Full box quantity	10 pc
Lamp's warm-up time to 60%	1
Length	1550 mm
Width	115 mm
Height	60 mm
Energy class	A++
Power	90 W
Voltage	185-265 V AC
Correlated colour temperature	4000 K

LED line LITE

Code: 477637

EAN: 5907777477637

LED line LITE TRI-PROOF 90W 4000K
1550mm


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	1550 mm
Height	60 mm mm
Length	115 mm mm
Weight	1,2 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	1560 mm mm
Height of collective packaging	260 mm
Length	320 mm mm
Weight	12,35 kg
Volume	0,129 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	100
Quantity collective euro pallet	630 szt.
Weight of a euro pallet	778,05 kg kg
Pallet height	1820 mm
Quantity in 1 layer	90 szt.
Number of layers	7

LED line LITE

Code: 477637

EAN: 5907777477637

**LED line LITE TRI-PROOF 90W 4000K
1550mm**

Example application