

code: 477323 EAN: 5907777477323

LEDOM Garden garland E27 5m + 10 x E27 1W

One of the most universal products in LEDOM catalogue, which you can use in both indoor and outdoor spaces. In winter, the garden festoon lighting E27 5m + 10 x E27 1W will make an extraordinary decoration inside your home, in a café or a restaurant, while in summer it will prove to be a gorgeous garden, terrace or arbour decoration. The garden festoon lighting E27 allows you to create cosy atmosphere in any space that you want to be well lit and extraordinarily decorated. Soft white light (colour temperature: 2700K) magnificently illuminates any space. Long, five metre rope guarantees energy-efficient lighting with 10W output for 10 LED filament light sources with E27 thread and additional protection positioned 0,5 metre apart.

Wide 270° lighting angle effectively disperses light around any source, resulting in pleasant glow that does not blind the user.

The IP65 protection class guarantees versatile use of the festoon lighting and allows it to be used indoor, as well as outside the building, without worries about changing weather conditions. The festoon lighting with high waterproof characteristics is also resistant to:

- snow,
- rain,
- sun,
- wind

The lampshades of light sources are made from highgrade polycarbonate, resistant to mechanical damage, and guarantee many years of durability and a lifetime of 20,000 hours.

The product is covered by 2-year manufacturer warranty.



Manufacturer issues a 2-year warranty for this product.



Beam angle




Ambient temperature suitable for operation

| Parameter | Value |
|-------------------------------|---------------|
| Power | 10 W |
| Colour of the light | White |
| IP protection rating | 65 |
| Warranty (years) | 2 |
| Input voltage range | 220 - 240 V |
| Input voltage frequency range | 50/60 HZ |
| Beam angle | 270 ° |
| Material (cover) | polycarbonate |


| Parameter | Value |
|--|--------------|
| Lifespan | 20000 |
| Power Factor | 0,5 |
| Number of on/off cycles | 15000 |
| Ambient temperature suitable for operation | `-20 ÷ 40 °C |
| Lamp's warm-up time to 60% | 1 |
| Length | 5000 mm |
| Useful luminous flux Φuse (EPREL) | 55 |




Single packaging



Bulk packaging



Europallet



7