

# LED bulb E14 9W 6500K 1170lm 170-250V C37 CANDLE DIMMABLE PRIME



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



Material (housing)



LED type



Dimmable



The structural design of this product ensures effective heat dissipation.



Number of on/off cycles



Voltage range and voltage type



Lamp type



Material (cover)



Lifespan




IP protection rating

Parameter	Value
Luminous efficacy	130 lm/W
Power	9 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	1170 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
Maximum power of the bulb	1170 W
IP protection rating	20
Warranty (years)	5
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	30 000
Application	Frosted
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	96


Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	0.9
Lamp's diameter	37
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Compatible dimmer type	TRIAC
Lifespan	30000
Power Factor	0,7
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7

**Single packaging**




Width	68 mm
Height	142 mm
Length	68 mm
Weight	0,06 kg
	1

**Bulk packaging**



Number of pieces/tape in meters pack zb	100 szt.
Width	500 mm
Height of collective packaging	270 mm
Length	255 mm
Weight	7 kg
Volume	0,034 m <sup>3</sup>

**Europallet**



Quantity collective euro pallet	4200 szt.
Weight of a euro pallet	294 kg
Pallet height	1890 mm
Quantity in 1 layer	600 szt.
Number of layers	7