

LED line PRIME

Code: 204171

EAN: 5905378204171

Linear luminaire FUSION 4000K 40W
5200lm 60°x110° IP20 120cm white PRIME
0-10V



FUSION LED line PRIME 40W and 5200 lm offers excellent lighting thanks to the colour temperature 4000K and the light distribution angle 60°x110°. The 0-10V dimming device has a high light efficiency of 130 lm/W. Made of durable aluminum, the body provides optimal heat discharge, which translates into a long life.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside

LED line PRIME


Code: 204171

EAN: 5905378204171


Linear luminaire FUSION 4000K 40W
5200lm 60*110° IP20 120cm white PRIME
0-10V

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	1158 mm
Height	52 mm
Length	70 mm
Weight	1,82 kg

Bulk packaging

Quantity	12
Width	1260 mm
Height	260 mm
Length	260 mm
Volume	0,085 m3
Weight	22,09 kg
Comments	

Europallet

Quantity	288
Height	1260 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	265,2 kg

LED line PRIME

Code: 204171

EAN: 5905378204171

**Linear luminaire FUSION 4000K 40W
5200lm 60*110° IP20 120cm white PRIME
0-10V**

Example application