


LED line PRIME

Code: LL-60-24

EAN: 5905378200166

**Power Supply 60-24 IP67 60W 24V PRIME**

The PRIME 60-24 IP67 LED line power supply is an efficient power supply with 60W and 24V output voltage. The operating area includes an input voltage range of 90 to 264V AC and a frequency of 47 to 63Hz. IP67 protection class provides high resistance to moisture and dust, making it ideal for applications in difficult conditions. The power factor PF is 0.95 and the efficiency reaches 0.84.



**Technical data**

Parameter	Value
Warranty	5
Power	• 60 W
Voltage	• 90-265 V AC
IP protection rating	IP67
IEC protection class	II
Output current range	0 ÷ 2.5
Input voltage frequency range	50 ÷ 60Hz
Rated current	0,275
Safety standards	IP67
Efficiency	0,84

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Power Factor	>=0,95
Ambient temperature suitable for operation	-30÷50
Height	32 mm
Output voltage	• 24 V


LED line PRIME

Code: LL-60-24

EAN: 5905378200166


**Power Supply 60-24 IP67 60W 24V  
PRIME**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,43 kg

**Bulk packaging**

Quantity	40
Width	205 mm
Height	215 mm
Length	385 mm
Weight	17,5 kg

**Europallet**

Quantity	1920
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	48
Weight	865 kg

---

LED line PRIME

Code: LL-60-24

EAN: 5905378200166

**Power Supply 60-24 IP67 60W 24V  
PRIME**

---

**Example application**