LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V PRIME

The PRIME 60-24 IP67 LED line power supply is an efficient power supply with 60W and 24V output voltage. The operating area includes an input voltage range of 90 to 264V AC and a frequency of 47 to 63Hz. IP67 protection class provides high resistance to moisture and dust, making it ideal for applications in difficult conditions. The power factor PF is 0.95 and the efficiency reaches 0.84.

5 WARRANTY | IP 67 | PF 0,95 | 24V DC | MAX -30÷70°C | CE

Technical data

Parameter	Value
Warranty	5
Power	• 60 W
Voltage	• 90-265 V AC
IP protection rating	IP67
IEC protection class	II
Output current range	0 ÷ 2.5
Input voltage frequency range	50 ÷ 60Hz
Rated current	0,275
Safety standards	IP67
Efficiency	0,84

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Power Factor	>=0,95
Ambient temperature suitable for operation	-30÷50
Height	32 mm
Output voltage	• 24 V

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V PRIME

Technical drawing



Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,43 kg



Bulk packaging

Quantity	40
Width	270 mm
Height	270 mm
Length	510 mm
Weight	21 kg



Europallet

Quantity	1920
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	50
Weight	865 kg

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V PRIME

Example application

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**