

LED line PRIME

Code: 203273-DALI

EAN: 5905378224254

**Linear luminaire FUSION 4000K 60W  
7800lm 120° IP20 150cm white PRIME  
PC Cover DALI**



**FUSION fixture series** is available in power ranges from 20 to 60W, with a color temperature of **4000K**. The efficiency of the fixtures is 130 lm/W.

**DALI version.**

**Product made to order - delivery within 4 days.**



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Dimmable function	Dali
Sling length	200 cm
Frequency of the supply voltage	50/60Hz
Beam angle	120°
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20 ÷ 45
For indoor use	Inside
Height	52 mm
DALI	• YES

LED line PRIME


Code: 203273-DALI

EAN: 5905378224254

**Linear luminaire FUSION 4000K 60W  
7800lm 120° IP20 150cm white PRIME  
PC Cover DALI**



**Technical drawing**

**Light distribution**



**Additional product photos**

**Logistics data**



**Single packaging**

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg

**Bulk packaging**

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Weight	22,6 kg

**Europallet**

Quantity	144
Height	1550 mm
Bulk quantity	12
Weight	286,8 kg

---

LED line PRIME

Code: 203273-DALI

EAN: 5905378224254

**Linear luminaire FUSION 4000K 60W  
7800lm 120° IP20 150cm white PRIME  
PC Cover DALI**

---

Example application