

LED line PRIME

product_card.label_product_code: 242885
product_card.label_product_gtin: 5901583242885

Downlight round adjustable die cast aluminium satin



product_card.label_technical_data

product_card.label_attribute_name	product_card.label_attribute
Maximum suitable lamp power	35
IP protection rating	IP20
Warranty (years)	5
Colour	satin
Fixture's diameter	92
Lamp's diameter	50
Material (housing)	DIE-CAST alu
Y-axis angle regulation	45

product_card.label_attribute_name	product_card.label_attribute
Type of surface suitable for installation	F
Distance from illuminated surface	0.5
Installation method	recessed
Mounting hole diameter	80 mm
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	100 pc
Height	30 mm

LED line PRIME

product_card.label_product_code: 242885
product_card.label_product_gtin: 5901583242885

Downlight round adjustable die cast aluminium satin




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



product_card.label_single_package

Width	100 mm
Height	105 mm mm
Length	40 mm mm
Weight	0,07 kg kg
	1

product_card.label_collective_package

Number of pieces/tape in meters pack zb	100 szt.
Width	520 mm mm
Height of collective packaging	220 mm
Length	440 mm mm
Weight	10 kg kg
Volume	0,050 m3 m3

product_card.label_europalette

Number of pieces/tapes in meters euro pallet	2100
Quantity collective euro pallet	1600 szt.
Weight of a euro pallet	160 kg kg
Pallet height	1760 mm
Quantity in 1 layer	200 szt.
Number of layers	8

LED line PRIME

product_card.label_product_code: 242885 product_card.label_product_gtin: 5901583242885

Downlight round adjustable die cast aluminium satin

product_card.label_realization_photo