


LED line PRIME

Code: LL-100-24

EAN: 5907777479259

**Power Supply 100-24 IP67 100W 24V PRIME**

The PRIME 100-24 IP67 LED line power supply is a highly efficient power supply that provides a stable 24V voltage and output power of 100.8W. Thanks to IP67 leak class, the device is weather resistant, which guarantees long-term use in difficult environments. It operates in a wide range of input voltage from 90 to 264V AC and 47-63Hz frequency. A high efficiency of 0.87 confirms energy economics.



**Technical data**

Parameter	Value
Warranty	5
Power	• 100 W
Voltage	• 90-264 V AC
IP protection rating	IP67
IEC protection class	II
Output current range	0 ÷ 4.2A
Input voltage frequency range	50 ÷ 60Hz
Rated current	0,46
Safety standards	IP67
Efficiency	0,87

Parameter	Value
Voltage tolerance	-/+5.0%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	35A / 230VAC
Power Factor	>0,95
Ambient temperature suitable for operation	-30÷50
Height	37 mm
Output voltage	• 24 V


LED line PRIME

Code: LL-100-24

EAN: 5907777479259


**Power Supply 100-24 IP67 100W 24V  
PRIME**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	60 mm
Height	45 mm
Length	215 mm
Weight	0,63 kg

**Bulk packaging**

Quantity	30
Width	205 mm
Height	230 mm
Length	425 mm
Weight	22,4 kg

**Europallet**

Quantity	1200
Height	1,90 m
Quantity in layer	300
Number of layers	4
Bulk quantity	60
Weight	1344 kg

---

LED line PRIME

Code: LL-100-24

EAN: 5907777479259

**Power Supply 100-24 IP67 100W 24V  
PRIME**

---

**Example application**