

LED line LITE

Code: 243936

EAN: 5901583243936

**LED bulb G4 6000K 2W 140lm 12V
AC/DC 120° LITE**



LED bulb G4 2W 6000K 140lm from LED line LITE is an innovative light source that emits a white, cool shade at a colour temperature of 6000 K. Thanks to the SMD2835 technology used, it reaches a luminous flux of 140 lm at only 2 W power. It is characterized by a light angle of 120°, which ensures wide scattering of the light.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 2 W
Voltage	• 12 V AC/DC
Correlated colour temperature	• 6000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	70
Luminous flux	140 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120°
Lifespan	50 000 h
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30

LED line LITE

Code: 243936

EAN: 5901583243936


**LED bulb G4 6000K 2W 140lm 12V
AC/DC 120° LITE**

Technical drawing

Light distribution


Additional product photos

Logistics data




Single packaging

Quantity	1
Width	30 mm
Height	9 mm
Length	42 mm
Weight	0,005 kg



Bulk packaging

Quantity	1000
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m ³
Weight	3,485 kg
Comments	



Europallet

Quantity	54000
Height	1880 mm
Quantity in layer	8000
Number of layers	8
Bulk quantity	64000
Weight	342,4 kg

LED line LITE

Code: 243936

EAN: 5901583243936

**LED bulb G4 6000K 2W 140lm 12V
AC/DC 120° LITE**

Example application