

LED line LITE

Code: 477606

EAN: 5907777477606

**Hermetic luminaire TRI-PROOF 4000K
30W 3600lm IP65 60cm gray LITE**



The TRI-PROOF 30W 4000K 650mm LED line LITE is a modern lighting solution, combining high performance and aesthetics. When emitting a light stream of 3600 lm, the lamp has a luminous efficiency of 120 lm/W. It offers a comfortable neutral colour of light at 4000 K and a wide light angle of 120°.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 30 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	120
Luminous flux	3600
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Standby power	0
Mounting type	surface
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
LED type	2835
LED quantity	96
Lifespan	35 000 h
Power Factor	0,9
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Height	48 mm
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line LITE

Code: 477606


EAN: 5907777477606

**Hermetic luminaire TRI-PROOF 4000K
30W 3600lm IP65 60cm gray LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	650 mm
Height	48 mm
Length	82 mm
Weight	0,4 kg

Bulk packaging

Quantity	10
Width	270 mm
Height	190 mm
Length	660 mm
Volume	0,033 m3
Weight	7,35 kg
Comments	

Europallet

Quantity	300
Height	1,8 m
Quantity in layer	60
Number of layers	5
Bulk quantity	30
Weight	250 kg

LED line LITE

Code: 477606

EAN: 5907777477606

**Hermetic luminaire TRI-PROOF 4000K
30W 3600lm IP65 60cm gray LITE**

Example application