


LED line LITE TRI-PROOF 30W 4000K 650mm



For indoor and outdoor use



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Flicker Free



Beam angle



Ambient temperature suitable for operation



Lifespan



The "fast-connect" fitting allows the user to connect power to the lamp in timely and easy manner and guarantees a waterproof protection of the power cable connection.



Manufacturer issues a 3-year warranty for this product.



For indoor and outdoor use



Voltage range and voltage type



LED type



LED quantity

Parameter	Value
ULOR	10%
Luminous efficacy	120 lm/W
Power	30 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	3600 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Standby power	0
IP protection rating	65
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Mounting type	surface
Supply voltage range and voltage type	185-265 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
Colour	White

Parameter	Value
Beam angle	120 °
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
LED type	2835
LED quantity	96
Lifespan	35000
Power Factor	0,9
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	08
Full box quantity	10 pc
Lamp's warm-up time to 60%	1
Length	650 mm
Width	82 mm
Height	48 mm
Product weight with packaging	382 g


The lumen maintenance factor

96 %

Energy class


A++

Single packaging




Width 82 mm
Height 50 mm
Length 650 mm
1

Bulk packaging



Outer box quantity 10 pcs.
Width 660 mm
Length 270 mm
Volume 0,039 m3

Europallet



Weight of a euro pallet 36
172,8 kg
4
9