

LED line PRIME

Code: LL-200-24

EAN: 5907777479334

LED power supply LED line PRIME LL-200-24 IP67 24V



Technical data


Parameter	Value	Parameter	Value
Output current range	0 ÷ 8.3A	Insulation strength	3kVAC
Warranty (years)	5	EMC standards	EN55015
Input voltage frequency range	47 ÷ 63Hz	Mounting type	surface
Rated current	8,3A	Inrush current (typ.)	30A / 230VAC
Safety standards	IP67	Ambient temperature suitable for operation	-30÷70 °C
Efficiency	0,90	IEC protection class	II
Voltage tolerance	-/+5.0%	Power	• 199.2 W
Ambient humidity	20 ÷ 95%	Voltage	• 200-264 V AC

LED power supply LED line PRIME LL-200-24 IP67 24V


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	85
Height	55 mm
Length	280 mm
Weight	1,17 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	15
Width	295 mm
Height of collective packaging	190
Length	455 mm
Weight	18,5 kg



Europallet

Number of pieces/tapes in meters euro pallet	480
Quantity collective euro pallet	32
Weight of a euro pallet	602 kg
Pallet height	1010

---

LED line PRIME

Code: LL-200-24

EAN: 5907777479334

**LED power supply LED line PRIME LL-  
200-24 IP67 24V**

---

**Example application**