LED line PRIME

Code: LL-200-24

EAN: 5907777479334

Power Supply 200-24 IP67 200W 24V PRIME

The PRIME 200-24 IP67 LED line power supply is a high quality device with an output power of 199.2 W, adapted for operation in difficult outdoor conditions thanks to IP67 leak class. It offers an output voltage of 24 V DC and an output current of up to 8.3 A, which provides stable power for a variety of LED applications. It has a high efficiency of 90% and a power factor of 0.95.

5 WARRANTY | IP 67 | PF 0,95 | 24V DC | MAX -30÷70°C | CE

Technical data

Parameter	Value
Warranty	5
Power	• 199.2 W
Voltage	• 200-264 V AC
IEC protection class	II
Output current range	0 ÷ 8.3A
Input voltage frequency range	47 ÷ 63Hz
Rated current	8,3A
Safety standards	IP67
Efficiency	0,90

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 95%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	30A / 230VAC
Ambient temperature suitable for operation	-30÷70
Output voltage	• 24 V

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-200-24

EAN: 5907777479334

Power Supply 200-24 IP67 200W 24V PRIME

Technical drawing



Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	85 mm
Height	55 mm
Length	280 mm
Weight	1,17 kg



Bulk packaging

Quantity	15
Width	295 mm
Height	190 mm
Length	455 mm
Weight	18,5 kg



Europallet

Quantity	480
Height	1,90 m
Quantity in layer	160
Number of layers	3
Bulk quantity	32
Weight	913 kg

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-200-24

EAN: 5907777479334

Power Supply 200-24 IP67 200W 24V PRIME

Example application

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**