

LED line LITE

Code: 247804

EAN: 5901583247804

LED line MR16 3W 2700K 273lm 10-14V
AC/DC 36°



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	91 lm/W	LED type	SMD2835
Colour of the light	White	Lifespan	30000
Energy efficiency class 2019/2015	F	Power Factor	0,4
Luminous flux	273 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
Warranty (years)	3	Ambient temperature suitable for operation	-20÷40 °C
Survival factor	0.9	For indoor use	Inside
Lifetime L70B50	30 000	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	50 mm
The lumen maintenance factor	96 %	Energy class	A++
Lamp's diameter	50	Power	• 3 W
Beam angle	36 °	Voltage	• 10-14 V AC/DC
Material (housing)	Glass	Correlated colour temperature	• 2700 K

LED line LITE


Code: 247804

EAN: 5901583247804


LED line MR16 3W 2700K 273lm 10-14V
AC/DC 36°

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	40 mm
Height	40 mm mm
Length	104 mm mm
Weight	0,06 kg kg
	10



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	595 mm mm
Height of collective packaging	170 mm
Length	290 mm mm
Weight	6,5 kg kg
Volume	0,029 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	4500
Quantity collective euro pallet	4400 szt.
Weight of a euro pallet	286 kg kg
Pallet height	1870 mm
Quantity in 1 layer	400 szt.
Number of layers	11

LED line LITE

Code: 247804

EAN: 5901583247804

**LED line MR16 3W 2700K 273lm 10-14V
AC/DC 36°**

Example application