

## LED line PRIME LED bulb E14 9W 4000K 1260lm 170-250V C37 Candle



5-year warranty

Manufacturer issues a 5-year warranty for this product.



220 °

Beam angle

MAX  
-20+40 °C

Ambient temperature suitable for operation



SMD2835

LED type

GOOD HEAT  
DISSIPATION

The structural design of this product ensures effective heat dissipation.

voltage  
170-250 VAC

Voltage range and voltage type



C37

Lamp type


30 000  
L70B50

Lifespan

Parameter	Value
Luminous efficacy	140 lm/W
Power	9 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1260 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %

Parameter	Value
Lamp's type	C37
Lamp's diameter	37
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7

**Single packaging**




Width	68 mm
Height	142 mm
Length	68 mm
Weight	0,06 kg
	1

**Bulk packaging**



Number of pieces/tape in meters pack zb	100 szt.
Width	500 mm
Height of collective packaging	270 mm
Length	255 mm
Weight	7 kg
Volume	0,034 m <sup>3</sup>

**Europallet**



Number of pieces/tapes in meters euro pallet	25000
Quantity collective euro pallet	4200 szt.
Weight of a euro pallet	294 kg
Pallet height	1890 mm
Quantity in 1 layer	600 szt.
Number of layers	7