

LED line PRIME

Code: 205833-AW3HAT

EAN: 5905378216631

Panel Backlit 34W 4000K 4760lm
UGR<19 60x60 Emergency module
PRIME AW3HAT



The 34W Backlit PRIME LAW3HAT panel emits a white light with a colour temperature of 4000K generates an impressive luminous flux of 4760 lm, which ensures high luminous efficiency of 140 lm/W. With UGR value<19 guarantees comfortable working conditions, minimizing the glare. The built-in emergency module allows up to 3 hours in case of power outage. Aluminium housing and polystyrene lid material provide an aesthetic appearance and durability.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<ul style="list-style-type: none">34 W
Voltage	<ul style="list-style-type: none">200-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Emergency module test	Auto Test
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 205833-AW3HAT

EAN: 5905378216631

**Panel Backlit 34W 4000K 4760lm
UGR<19 60x60 Emergency module
PRIME AW3HAT**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 205833-AW3HAT

EAN: 5905378216631

**Panel Backlit 34W 4000K 4760lm
UGR<19 60x60 Emergency module
PRIME AW3HAT**

Example application

