

LED line PRIME

Code: 203259

EAN: 5905378203259

**Linear luminaire FUSION 4000K 20W
2600lm 120° IP20 60cm white PRIME PC
Cover**



LED line mount PRIME FUSION 20W 4000K is an innovative solution characterized by 2600 lm light stream and 130 lm/W efficiency. Made of durable aluminum, it provides excellent heat dissipation. Key parameters are a light distribution angle of 120°, IP20 leak class and 0.9 PF power factor. The product is covered by a five-year warranty, which confirms its high quality and durability in use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52

LED line PRIME

Code: 203259


EAN: 5905378203259

**Linear luminaire FUSION 4000K 20W
2600lm 120° IP20 60cm white PRIME PC
Cover**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg

Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	11,5 kg
Comments	

Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

LED line PRIME

Code: 203259

EAN: 5905378203259

**Linear luminaire FUSION 4000K 20W
2600lm 120° IP20 60cm white PRIME PC
Cover**

Example application