

LED line PRIME

Code: LL-50-12

EAN: 5905378206694

LED power supply LED line PRIME LL-50-12 IP67 12V



Technical data

Parameter	Value	Parameter	Value
Output current range	0 ÷ 5A	EMC standards	EN55015
Warranty (years)	5	Mounting type	surface
Input voltage frequency range	47 ÷ 63Hz	Inrush current (typ.)	70A / 230VAC
Rated current	5A	Power Factor	0,95
Safety standards	IP67	Ambient temperature suitable for operation	-30÷70 °C
Efficiency	0,84	IEC protection class	II
Voltage tolerance	-/+5.0%	Power	• 60 W
Ambient humidity	20 ÷ 90%	Voltage	• 90-264 V AC
Insulation strength	3kVAC		

LED line PRIME

Code: LL-50-12

EAN: 5905378206694


LED power supply LED line PRIME LL-50-12 IP67 12V

Dimensions

Light distribution


Additional product photos

Logistics data




Single packaging

Width	52
Height	35 mm
Length	185 mm
Weight	0,39 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	50
Width	275 mm
Height of collective packaging	195
Length	385 mm
Weight	20,5 kg



Europallet

Number of pieces/tapes in meters euro pallet	2400
Quantity collective euro pallet	48
Weight of a euro pallet	994 kg
Pallet height	1200

---

LED line PRIME

Code: LL-50-12

EAN: 5905378206694

**LED power supply LED line PRIME LL-50-12 IP67 12V**

---

**Example application**