



LED line PRIME

Code: LL-50-12

EAN: 5905378206694

Power supply 50-12 IP67 50W 12V PRIME

LED power supply 50W IP67 12V PRIME by LED line is a high-performance device with an output power of 60W and a output voltage of 12V. IP67 leak class provides effective protection against water and dust, making it ideal for applications under difficult conditions. The power supply has a power factor of 0.95 and an efficiency of 0.84. It works in a wide range of input voltages from 90 to 264V AC. The warranty on the product is five years.



Technical data

Parameter	Value
Warranty	5
Power	• 60 W
Voltage	• 90-264 V AC
IEC protection class	II
Output current range	0 ÷ 5A
Input voltage frequency range	47 ÷ 63Hz
Rated current	5A
Safety standards	IP67
Efficiency	0,84

Parameter	Value
Voltage tolerance	-/+5,0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Power Factor	0,95
Ambient temperature suitable for operation	-30÷70
Output voltage	• 12 V


LED line PRIME

Code: LL-50-12

EAN: 5905378206694

Power supply 50-12 IP67 50W 12V PRIME



Technical drawing



Light distribution

Additional product photos

Logistics data



Single packaging

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,39 kg

Bulk packaging

Quantity	40
Width	275 mm
Height	195 mm
Length	385 mm
Weight	17,3 kg

Europallet

Quantity	2400
Height	1200 mm
Bulk quantity	48
Weight	994 kg

LED line PRIME

Code: LL-50-12

EAN: 5905378206694

Power supply 50-12 IP67 50W 12V PRIME

Example application