LED line PRIME

Code: LL-400-24-ALU

EAN: 5905378229020

# Power supply 400-24 IP67 400W 24V Aluminum PRIME



Constant voltage power supplies LED line from the PRIME series with a power of 300W and 400W (24V) are powerful devices designed for professional, extensive lighting projects. They guarantee the highest energy efficiency and reduce heat losses, which translates into stable and exceptionally economical operation of your installation. The durable aluminum housing with an IP67 protection class ensures complete protection against water and dust, while two current outputs guarantee quick and convenient installation of the system.

5 WARRANTY

IP 67

## Technical data

| Parameter | Value |
|---|---|
| Warranty | 5 |
| Voltage | • 220-240 V AC |
| IP protection rating | IP67 |
| IEC protection class | I |
| Output current range | 0-16,6 A |
| Output current | 16,6 A |

| Parameter | Value |
|---|---|
| Rated current | 1,83 A |
| Frequency of the supply voltage | 50/60Hz |
| Power Factor | >=0,95 |
| Ambient temperature suitable for operation | -20÷45 |
| Height | 34 mm |
| Output voltage | • 24 V |



T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-400-24-ALU

EAN: 5905378229020

# Power supply 400-24 IP67 400W 24V Aluminum PRIME

### Technical drawing




### Light distribution

## Additional product photos





## Logistics data



### Single packaging

| | |
|---|---|
| Width | 95 mm |
| Height | 37 mm |
| Length | 334 mm |
| Weight | 1.62 kg |



### Bulk packaging

| | |
|---|---|
| Quantity | 14 |
| Width | 340 mm |
| Height | 135 mm |
| Length | 480 mm |
| Weight | 21kg |



### Europallet

| | |
|---|---|
| Quantity | 630 |
| Height | 1,5 m |
| Bulk quantity | 14 |
| Weight | 980 kg |



T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME

Code: LL-400-24-ALU

EAN: 5905378229020

# Power supply 400-24 IP67 400W 24V Aluminum PRIME

**Example application**



T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**