

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE



The 40W Backlit Panel 2in1 emitting white light with temperature of 4000K provides excellent lighting thanks to a light stream of 4000 lumens. The panel dimensions are standard 62x62 cm design, ideal for different interiors. Equipped with an emergency module with up to three hours working time, it provides reliability in emergency situations.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80

Parameter	Value
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polystyrene
Material (housing)	Metal
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	I
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 40 W

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

**Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

**Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE**

Example application