

LED line PRIME


Code: 479594-AW3HAT

EAN: 5905378212220

LINKER TRI-PROOF 40W 4000K 6000lm
150lm/W IP65 120cm Emergency
module 3H AT PRIME



LINKER 40W from LED line PRIME is an advanced lighting solution that combines high energy efficiency with elegant design. It emits a light stream of 6000 lm with excellent performance of 150 lm/W. IP65 leak class and IK08 resistance provide reliability even in difficult conditions. Life of up to 100000 hours and Ra colour rendering rate ≥ 80 guarantee comfort of use and natural color reproduction.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Autotest
ULOR	3 %
Voltage	• 200-240 V AC
Luminous efficacy	150
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	6000
Colour consistency in McAdam ellipses	≤ 6
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	Grey

Parameter	Value
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
LED type	SMD2835
Lifespan	100 000 h
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤ 6
Ambient temperature suitable for operation	$-25 \div 45$
IEC protection class	II
IK protection rating	08
Lamp's warm-up time to 60%	1 s
Energy class	A+
Correlated colour temperature	• 4000 K
Power	• 40 W

LED line PRIME

Code: 479594-AW3HAT


EAN: 5905378212220

**LINKER TRI-PROOF 40W 4000K 6000lm
150lm/W IP65 120cm Emergency
module 3H AT PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 479594-AW3HAT

EAN: 5905378212220

**LINKER TRI-PROOF 40W 4000K 6000lm
150lm/W IP65 120cm Emergency
module 3H AT PRIME**

Example application