

LED line LITE

Code: 211612-II



EAN: 5905378220126

**LINIX 4000K 45W 5400lm IP65 150cm gray LITE**



LINIX LITE is a modern LED fixture with high energy efficiency and durability. With a luminous efficacy of 120 lm/W and a wide beam angle of 120° it provides even and comfortable lighting. The built-in microwave motion sensor (30lx; 30 sec.; 4m; 120°) allows for light control only when needed,

The fixtures can be connected into continuous light lines - up to 12 fixtures, allowing for flexible adaptation of lighting to large spaces. With easy installation and solid construction, LINIX LITE is an excellent choice for demanding users.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 45 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
IP protection rating	IP65
IEC protection class	II
Luminous efficacy	120
Luminous flux	5400
Lifetime L70B50	20 000 h

Parameter	Value
Standby power	0
Mounting type	surface
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
Power Factor	0,95
Ambient temperature suitable for operation	-20/+40
Height	35 mm
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polystyrene


LED line LITE

Code: 211612-II

EAN: 5905378220126

**LINIX 4000K 45W 5400lm IP65 150cm  
gray LITE**

**Technical drawing**



**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	
Width	51 mm
Height	25 mm
Length	1575 mm
Weight	0,363 kg

**Bulk packaging**

Width	275 mm
Height	230 mm
Length	1580 mm
Weight	11,9 kg
Comments	

**Europallet**

Quantity	360
Height	1900 mm
Quantity in layer	12
Number of layers	1
Bulk quantity	12
Weight	180 kg

LED line LITE

Code: 211612-II

EAN: 5905378220126

**LINIX 4000K 45W 5400lm IP65 150cm  
gray LITE**

**Example application**

