

LED line LITE

Code: 203501

EAN: 5905378203501

LED line LITE Floodlight PHOTON 10W
4000K 1000lm with motion sensor



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	Sensor type	PIR
Colour of the light	White	Material (cover)	tempered glass
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	Min 5 lx - Max 2000 lx	Material (housing)	DIE-CAST alu
Energy efficiency class 2019/2015	F	LED type	SMD2835
Luminous flux	1000 lm	LED quantity	15
Colour consistency in McAdam ellipses	≤6	Power Factor	0,7
IP protection rating	IP65	Number of on/off cycles	18000
Warranty (years)	3	Colour consistency in McAdam ellipses	≤6
Survival factor	0.9	Ambient temperature suitable for operation	-20÷40 °C
Lifetime L70B50	30 000	For indoor and outdoor use	YES
Rated power	220-240V AC	IEC protection class	I
Weight	215 g	IK protection rating	05
Mounting type	surface	Lamp's warm-up time to 60%	1
Mounting height	2.3-5.0m	Length	105 mm
Frequency of the supply voltage	50/60Hz	Width	62 mm
Colour rendering index Ra	80	Height	137 mm
Colour	Black	Power	• 10 W
The lumen maintenance factor	96 %	Voltage	• 220-240 V AC
Beam angle	120 °	Correlated colour temperature	• 4000 K

LED line LITE

Code: 203501


EAN: 5905378203501

LED line LITE Floodlight PHOTON 10W
4000K 1000lm with motion sensor




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	105 mm
Height	137 mm mm
Length	62 mm mm
Weight	0,27 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	24 szt.
Width	440 mm mm
Height of collective packaging	312 mm
Length	263 mm mm
Weight	6,83 kg
Volume	0,036 m3 m3

Europallet

Quantity collective euro pallet	135 szt.
Weight of a euro pallet	245,88 kg
Pallet height	1872 mm
Quantity in 1 layer	144 szt.
Number of layers	6

LED line LITE

Code: 203501

EAN: 5905378203501

**LED line LITE Floodlight PHOTON 10W
4000K 1000lm with motion sensor**

Example application