


# LED line LITE Bulb LED E27 12W 3000K 1212lm 230V A60



Voltage range and voltage type



Lifespan



Beam angle



Parameter	Value
Luminous efficacy	101 lm/W
Power	12 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	1212 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's diameter	60
Beam angle	240 °
Material (housing)	PVC
Lifespan	50000
Power Factor	0,5


Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Height	108 mm
Product weight with packaging (g)	30 g
EPREL ID	632 332
Date of first placement on the market	2020-04-01 00:06:55
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	4
Total luminous flux (EPREL)	1 212
On-mode power P <sub>on</sub> (EPREL)	12
Useful luminous flux Φ <sub>use</sub> (EPREL)	1 212
Beam angle in degrees (EPREL)	240

Single packaging



61  
61  
115  
0,0454  
1

Bulk packaging



100

Europallet



3