

LED line PRIME

Code: 211001

EAN: 5905378211001

LED line PRIME LED strip 528 COB 24V
3000K 14W 30m

ATG

F

New



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	LED type	COB
Colour of the light	White	LED quantity	2640
Energy efficiency class 2019/2015	F	Compatible dimmer type	PWM
Colour consistency in MacAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
Warranty (years)	5	LED quantity (lm)	528
Dimmable function	PWM	Cutting section	4,6
Survival factor	0.9	Type of adhesive tape	3M 300 LSE
Minimum purchase quantity	30	Colour consistency in MacAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-30÷45 °C
Wire length	200 mm	For indoor use	Inside
Wattage (lm)	14 W	IEC protection class	III
Luminous flux (lm)	1400	Length	30000 mm
Current (lm)	0,58	Width	10 mm
Colour rendering index Ra	90	Height	2 mm
Metres per roll	30 m	Power	• 14
The lumen maintenance factor	96 %	Voltage	• 24 V DC
Beam angle	180 °	Correlated colour temperature	• 3000 K

LED line PRIME

Code: 211001

EAN: 5905378211001


LED line PRIME LED strip 528 COB 24V
3000K 14W 30m

Dimensions


Light distribution

Additional product photos


Logistics data



Single packaging



Bulk packaging



Europallet

Number of pieces/tape in meters pack zb

LED line PRIME

Code: 211001

EAN: 5905378211001

**LED line PRIME LED strip 528 COB 24V
3000K 14W 30m**

Example application