

LED line PRIME


Code: 204522-010V

EAN: 5905378220591

**Backlit Panel 4000K 34W 4760lm  
62x62cm white UGR<19 PRIME 0-10V**



The LED line PRIME Backlit panel with a power of 34W and a color temperature of 4000K is an excellent solution for demanding applications. Generating a luminous flux of 4760 lumens, it provides efficient and energy-saving lighting, achieving an efficiency of 140 lm/W. With a low glare index UGR<19 and high-quality construction from aluminum and polystyrene, this product stands out for its durability and user comfort. LIFUD power supply with 0-10V control.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	64
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 204522-010V

EAN: 5905378220591




**Backlit Panel 4000K 34W 4760lm  
62x62cm white UGR<19 PRIME 0-10V**

Technical drawing

Light distribution

Additional product photos

**Logistics data**



**Single packaging**

Quantity	1
Width	35 mm
Height	640 mm
Length	630 mm
Weight	1,9 kg

**Bulk packaging**

Quantity	5
Width	200 mm
Height	655 mm
Length	645 mm
Volume	0,085 m <sup>3</sup>
Weight	12,5 kg
Comments	

**Europallet**

Height	1320 mm
Quantity in layer	30
Number of layers	2
Bulk quantity	60
Weight	150 kg

---

LED line PRIME

Code: 204522-010V

EAN: 5905378220591

**Backlit Panel 4000K 34W 4760lm  
62x62cm white UGR<19 PRIME 0-10V**

---

**Example application**