

LED line PRIME

Code: 204256

EAN: 5905378204256

**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME**



FUSION 60W linear luminaire from LED line PRIME provides excellent light quality with a temperature of 4000K and a light stream of 7800 lumens. The transmission angle is 120°, allowing even surface lighting. Made of durable aluminum, it has a high energy efficiency of 130 lm/W and a long service life of up to 50,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52


LED line PRIME

Code: 204256

EAN: 5905378204256

**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME**


Technical drawing



Light distribution


Additional product photos

Logistics data




Single packaging

Width	1444 mm
Height	32 mm
Length	70 mm
Weight	1,97 kg



Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	120 mm
Volume	0,048 m ³
Weight	23,89 kg
Comments	



Europallet

Quantity	144
Height	1820 mm
Quantity in layer	12
Number of layers	7
Bulk quantity	12
Weight	25 kg

LED line PRIME

Code: 204256

EAN: 5905378204256

**Linear luminaire FUSION 4000K 60W
7800lm 120*120° IP20 150cm white
PRIME**

Example application