

LED line LITE

Code: 248306

EAN: 5901583248306

LED line® LITE LED bulb GU10 5W
2700K 410lm 220-260V 50°



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	82 lm/W	LED type	SMD2835
Colour of the light	White	Lifespan	30000
Energy efficiency class 2019/2015	G	Power Factor	0,5
Luminous flux	410 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
Warranty (years)	3	Ambient temperature suitable for operation	-20÷40 °C
Survival factor	0.9	For indoor use	Inside
Lifetime L70B50	30 000	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	53 mm
The lumen maintenance factor	96 %	Energy class	A+
Lamp's diameter	50	Power	• 5 W
Beam angle	50 °	Voltage	• 220-260 V AC
Material (cover)	glass	Correlated colour temperature	• 2700 K
Material (housing)	Glass		

LED line LITE


Code: 248306

EAN: 5901583248306


LED line® LITE LED bulb GU10 5W
2700K 410lm 220-260V 50°

product_card.label_dimensions




product_card.label_curve_light



product_card.label_product_gallery



product_card.label_logistic_data



Single packaging

Width	40 mm
Height	40 mm mm
Length	104 mm mm
Weight	0,07 kg kg
	10

Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	595 mm mm
Height of collective packaging	170 mm
Length	290 mm mm
Weight	6,5 kg kg
Volume	0,029 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	4500
Quantity collective euro pallet	4400 szt.
Weight of a euro pallet	286 kg kg
Pallet height	1870 mm
Quantity in 1 layer	400 szt.
Number of layers	11

LED line LITE

Code: 248306

EAN: 5901583248306

**LED line® LITE LED bulb GU10 5W
2700K 410lm 220-260V 50°**

Example application