

1800

White



Manufacturer issues a 3-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Ambient temperature suitable for operation



Lifespan



This product is suitable for surface-mounted installation.



Voltage range and voltage type



LED type




LED quantity

Parameter	Value
Power	6 W
Colour of the light	White
Energy efficiency class 2019/2015	G
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	54
Warranty (years)	3
Survival factor	30000
Lifetime L70B50	30 000
Supply voltage range and voltage type	100- 260 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %

Parameter	Value
Beam angle	0-120 °
Material (cover)	glass
Material (housing)	aluminum
LED type	2835 SMD
LED quantity	14
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	II
IK protection rating	05

Single packaging



Width	110 mm
Height	110 mm
Length	110 mm
Weight	0,3 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	40 szt.
Width	570 mm
Height of collective packaging	460 mm
Length	240 mm
Weight	12,35 kg
Volume	0,062 m ³
	2

Europallet



Number of pieces/tapes in meters euro pallet	840
Quantity collective euro pallet	960 szt.
Weight of a euro pallet	296,4 kg
Pallet height	1840 mm
Quantity in 1 layer	240 szt.
Number of layers	4