


**LEDOM GU10 3W 6500K 240lm 220-240V**

Voltage range and voltage type



Lifespan



Beam angle



Parameter	Value
Luminous efficacy	80 lm/W
Power	3 W
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	240 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's diameter	50
Beam angle	120 °
Lifespan	50000
Power Factor	0,4

Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Height	55 mm
EPREL ID	632 314
Date of first placement on the market	2018-08-01 00:14:49
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	6
Total luminous flux (EPREL)	240
On-mode power P <sub>on</sub> (EPREL)	3
Useful luminous flux Φ <sub>use</sub> (EPREL)	240
Beam angle in degrees (EPREL)	120

Single packaging



52  
52  
59  
0,0286  
1

Bulk packaging



50

Europallet



4