LED line LITE

Code: 201439

EAN: 5905378201439

Ceiling Light 4000K 24W 1950lm round IP44 white LITE

24W LITE LED Plafon emits a bright, neutral light with a temperature of 4000K and a light stream of 1950 lm. Its light output reaches 81 lm/W, providing effective lighting. IP44 leak class protects against moisture and dust and Ra ≥ 80 colour reproduction factor guarantees faithful colour rendering. The product is simple to install and maintain, offering a durability of up to 30,000 working hours.

Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP44
IEC protection class	I
Luminous efficacy	81
Luminous flux	1950
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD 2835
LED quantity	28
Ambient temperature suitable for operation	-20÷40
Height	62
Fixture's diameter	380 mm
Colour	White

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line LITE | Code: 201439 | EAN: 5905378201439

Ceiling Light 4000K 24W 1950lm round IP44 white LITE

Technical drawing



Light distribution



Additional product photos

Logistics data







Single packaging

Quantity	1
Width	420 mm
Height	420 mm
Length	70 mm
Weight	0,56 kg

Bulk packaging

Quantity	12
Width	470 mm
Height	440 mm
Length	860 mm
Volume	0,177 m3
Weight	7,07 kg
Comments	

Europallet

Height	1760 mm
Quantity in layer	12
Number of layers	4
Bulk quantity	48
Weight	28,28 kg

LED line LITE | Code: 201439 | EAN: 5905378201439

Ceiling Light 4000K 24W 1950lm round IP44 white LITE

Example application