


code: 247330 EAN: 5901583247330

LED line® UFO T-Series 100-277V 200W 30000LM 4000K 120°DIM





High luminous efficacy ensured by high quality CREE branded LEDs.



This product is equipepd with a MEANWELL branded driver which ensures reliable and fault-free operation even during prolonged, continous running.

FLICKER FREE™ system guarantees no harmful flickering

effect and ensures safety for users' eyesight.

Ambient temperature suitable for operation



warranty

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.





The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.

<予> 120 °

Beam angle

мах **4**0÷45 °0

50 000 h

 \bigcirc L70850 Lifespan

Dimmable

| Parameter | Value |
|---------------------------------------|-------------|
| Luminous efficacy | 150 lm/W |
| Power | 200 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | D |
| Luminous flux | 30000 lm |
| Correlated colour temperature | 4000 K |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 65 |
| Warranty (years) | 5 |
| Dimmable function | 1-10 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 50 000 |
| Supply voltage range and voltage type | 100-277 VAC |
| Frequency of the supply voltage | 50/60Hz |
| Colour rendering index Ra | 70 |
| Colour | black |
| The lumen maintenance factor | 96 % |

Product weight with packaging 5450 g

```
LED line® export@ledline.pl www.ledline.pl/en
```



324

Voltage range and voltage type

LED type

LED quantity

| Parameter | Value |
|--|-----------|
| Material (housing) | aluminum |
| LED type | SMD3030 |
| LED quantity | 324 |
| Not dimmable | ТАК |
| Compatible dimmer type | 1-10V |
| Lifespan | 50000 |
| Power Factor | 0,95 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -40÷45 °C |
| For indoor and outdoor use | YES |
| IEC protection class | İ |
| IK protection rating | 08 |
| Full box quantity | 1 pc |
| Lamp's warm-up time to 60% | 1 |
| Height | 250 mm |
| Product weight with packaging | 5450 g |



| Lamp's diameter | 320 | Master carton weight (kg) | 54,5 |
|------------------|---------------|---------------------------|------|
| Beam angle | 120 ° | Energy class | A+ |
| Material (cover) | polycarbonate | | |

Luminous [cd/klm]

C0 - C180[°]**C90 - C270**

390 mm


390 mm

0,032 m3

6,08 kg

215


Single packaging



Width Height Length Weight

390 mm 215 mm 390 mm 6,08 kg 1

Bulk packaging



Width Length Weight Volume

Europallet



Weight of a euro pallet