


LED line LITE

Code: 211605

EAN: 5905378211605

LED line LITE LINIX 120cm 36W 4000K
4320lm IP65

New



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	120 lm/W	Material (housing)	Polycarbonate
Colour of the light	White	Lifespan	20000
Energy efficiency class 2019/2015	E	Power Factor	0,95
Luminous flux	4320 lm	Ambient temperature suitable for operation	-20÷40 °C
Colour consistency in McAdam ellipses	≤6	IEC protection class	II
IP protection rating	IP65	Full box quantity	30 pc
Survival factor	0,9	Lamp's warm-up time to 60%	1
Mounting type	mixed	Length	1237 mm
Frequency of the supply voltage	50/60Hz	Width	53 mm
Colour rendering index Ra	80	Height	27 mm
CRI colour rendering index	80	Power	• 36 W
The lumen maintenance factor	96 %	Voltage	• 220-240 V AC
Beam angle	120 °	Correlated colour temperature	• 4000 K
Material (cover)	polystyrene		

LED line LITE


Code: 211605

EAN: 5905378211605

LED line LITE LINUX 120cm 36W 4000K
4320lm IP65

Dimensions


Light distribution



Additional product photos




Logistics data




Single packaging

Width	51
Height	25 mm
Length	1275 mm
Weight	0,301 kg



Bulk packaging

Width	275 mm
Height of collective packaging	190
Length	1280 mm
Weight	9,9 kg



Europallet

Quantity collective euro pallet	480
Weight of a euro pallet	160 kg

LED line LITE

Code: 211605

EAN: 5905378211605

**LED line LITE LINIX 120cm 36W 4000K
4320lm IP65**

Example application