

LED line PRIME

Code: 206526

EAN: 5905378206526

LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295 0-10V



Backlit LED line PRIME panel with 34W power and 4000K light color perfectly combines modern technology with high energy efficiency. With an impressive light stream of 4760 lm and a low UGR index of<19, the setting provides comfortable visual conditions. The built-in 0-10V dimming system allows precise adjustment of the intensity of light, adjusting it to the user's needs.



Technical data

Parameter	Value
Voltage	• 200-240 V AC
Luminous efficacy	140
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	4760
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	0-10
Survival factor	0.9
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96

Parameter	Value
Beam angle	90
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 34 W

LED line PRIME

Code: 206526

EAN: 5905378206526


**LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295 0-10V**

**Technical drawing**




**Light distribution**


**Additional product photos**




**Logistics data**



**Single packaging**



**Bulk packaging**



**Europallet**

---

LED line PRIME

Code: 206526

EAN: 5905378206526

**LED line PRIME Panel Backlit 34W  
4000K 4760lm UGR<19 1195x295 0-10V**

---

**Example application**