

LED line PRIME

Code: 206526

EAN: 5905378206526

**Backlit Panel 4000K 34W 4760lm IP20
30x120cm white UGR<19 PRIME 0-10V**



The Backlit LED line PRIME panel with a power of 34W and a light color of 4000K perfectly combines modern technology with high energy efficiency. With an impressive luminous flux of 4760 lm and a low UGR<19 rating, the fixture provides comfortable visual conditions. The built-in 0-10V dimming system allows for precise adjustment of light intensity, tailoring it to the user's needs.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene


LED line PRIME

Code: 206526

EAN: 5905378206526

**Backlit Panel 4000K 34W 4760lm IP20
30x120cm white UGR<19 PRIME 0-10V**

Technical drawing



Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	32 mm
Height	305 mm
Length	1245 mm
Weight	1,56 kg



Bulk packaging

Quantity	5
Width	330 mm
Height	180 mm
Length	1265 mm
Volume	0,084 m3
Weight	10,5 kg
Comments	



Europallet

LED line PRIME

Code: 206526

EAN: 5905378206526

**Backlit Panel 4000K 34W 4760lm IP20
30x120cm white UGR<19 PRIME 0-10V**

Example application