

LED line PRIME

Code: 244216

EAN: 5901583244216

LED line strip 300 SMD 12V 6500K 7,2W
SIDE VIEW



product_card.label_technical_data

Parameter	Value
Luminous efficacy	76 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	G
Colour consistency in McAdam ellipses	≤3
IP protection rating	IP20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (lm)	7,2 W
Luminous flux (lm)	550lm
Current (lm)	0,6
Colour rendering index Ra	80
Metres per roll	5
The lumen maintenance factor	96 %
Beam angle	120 °
LED type	SMD3014
Not dimmable	TAK
Compatible dimmer type	PWM

Parameter	Value
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Cutting section	5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Energy class	A+
Power	• 7.2 W
Voltage	• 12 V DC
Correlated colour temperature	• 6500 K

LED line PRIME


Code: 244216

EAN: 5901583244216



LED line strip 300 SMD 12V 6500K 7,2W
SIDE VIEW

product_card.label_dimensions


product_card.label_curve_light




product_card.label_product_gallery




product_card.label_logistic_data



Single packaging



Bulk packaging



Europallet

Number of pieces/tape in meters pack zb 100

Number of pieces/tapes in meters euro pallet	960
Quantity collective euro pallet	24
Quantity in 1 layer	8
Number of layers	3

LED line PRIME

Code: 244216

EAN: 5901583244216

LED line strip 300 SMD 12V 6500K 7,2W
SIDE VIEW

Example application