

LED line PRIME


Code: 244216

EAN: 5901583244216

**LED strip 300/5m SMD 12V 6500K 7,2W  
IP20 SIDE VIEW 8mm 5m 550lm/m  
PRIME**



The 300 SMD LED line is an advanced light source, which has a power of 7.2 W per metre and a colour temperature of 6500 K. The use of SMD3014 diodes provides high light performance of up to 550 lm per metre. It allows dimming using PWM drivers, allowing to adjust the light intensity to individual needs.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	5
Power	• 7.2 W / m
Voltage	• 12 V DC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	III
Cutting section	5 cm
Luminous efficacy	76
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* - difference B10-B50 ≈ 1% (according to LightingEurope) - negligible	35000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤3
Luminous flux (lm)	550
Current (Im)	0,6
Beam angle	120
LED type	SMD3014
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Type of adhesive tape	3M 300 LSE
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	2,5

LED line PRIME


Code: 244216

EAN: 5901583244216

**LED strip 300/5m SMD 12V 6500K 7,2W  
IP20 SIDE VIEW 8mm 5m 550lm/m  
PRIME**




**Technical drawing**

**Light distribution**



**Additional product photos**

**Logistics data**



**Single packaging**

Quantity	5 m
Weight	0,085 kg

**Bulk packaging**

Quantity	100
Width	320 mm
Height	180 mm
Length	360 mm
Weight	4,16 kg
Comments	

**Europallet**

Quantity	960
Quantity in layer	8
Number of layers	3
Bulk quantity	24

---

LED line PRIME

Code: 244216

EAN: 5901583244216

**LED strip 300/5m SMD 12V 6500K 7,2W  
IP20 SIDE VIEW 8mm 5m 550lm/m  
PRIME**

---

Example application