

LED line LITE

Code: 201026

EAN: 5905378201026

LED line LITE Downlight MOLLY 24W
2550lm 4000K round with motion
sensor



Technical data

Parameter	Value
Luminous efficacy	105 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	2550 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Weight	180 g
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Lamp's diameter	220
Beam angle	110 °

Parameter	Value
Sensor type	Microwave
Material (housing)	Polycarbonate
LED type	SMD LED 2835
LED quantity	120
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
Mounting hole diameter	190-210 mm
For indoor use	Inside
IEC protection class	II
Height	26 mm
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K

LED line LITE

Code: 201026


EAN: 5905378201026

LED line LITE Downlight MOLLY 24W
2550lm 4000K round with motion
sensor




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	226 mm
Height	34 mm mm
Length	226 mm mm
Weight	0,2 kg kg

Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	472 mm mm
Height of collective packaging	472 mm
Length	390 mm mm
Weight	12,5 kg kg
Volume	0,086 m3 m3

Europallet

Quantity collective euro pallet	640 szt.
Weight of a euro pallet	200 kg
Pallet height	1888 mm
Quantity in 1 layer	160 szt.
Number of layers	4

LED line LITE

Code: 201026

EAN: 5905378201026

**LED line LITE Downlight MOLLY 24W
2550lm 4000K round with motion
sensor**

Example application



zdjęcie-realizacji.png