

LED line PRIME

Code: 227354-DALI


EAN: 5905378227941

**Downlight CALMOS 3CCT (3/4/6,5K)
24W 2800lm round IP54 White PRIME
DALI**



The new LED line Calmos 3CCT downlight is an ultra-slim fixture with a color temperature changing function, designed specifically for installation in low ceiling spaces. The external, replaceable power supply ensures optimal thermal conditions and allows for easy adaptation to lighting control systems. With an efficiency of 110lm/W and a 5-year warranty, it is a reliable choice for professionals looking for versatile and durable solutions.

DALI version - Waiting time up to 5 days.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6500 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	03
IEC protection class	II
Luminous efficacy	115
Luminous flux	2800

Parameter	Value
Lifetime L70B50	50 000 h
L80B* - difference B10-B50 ≈ 1% (according to LightingEurope) - negligible	35000 h
Frequency of the supply voltage	50/60Hz
Beam angle	110°
Power Factor	0,8
Ambient temperature suitable for operation	-20 ÷ 45
For indoor use	Inside
Height	40 mm
Fixture's diameter	175 mm
Colour	Biały
Material (housing)	Aluminium
DALI	• YES


LED line PRIME

Code: 227354-DALI

EAN: 5905378227941

**Downlight CALMOS 3CCT (3/4/6,5K)
24W 2800lm round IP54 White PRIME
DALI**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	50 mm
Height	190 mm
Length	180 mm
Weight	0,325 kg

Bulk packaging

Quantity	30
Width	525 mm
Height	205 mm
Length	555 mm
Weight	10,5 kg

Europallet

Quantity	540
Height	1,8 m
Bulk quantity	18
Weight	230 kg

LED line PRIME

Code: 227354-DALI

EAN: 5905378227941

**Downlight CALMOS 3CCT (3/4/6,5K)
24W 2800lm round IP54 White PRIME
DALI**

Example application