

LED line LITE


Code: 200753

EAN: 5905378200753

**DOWNLIGHT MOLLY 3000K 9W 830lm
round IP20 White LITE**



The 9W LITE Downlight MOLLY LED Line delivers 830 lumens and 3000K warm colour, ideal for different spaces. It is characterized by high light efficiency of 90 lm/W and Ra>80 colour rendering coefficient, which ensures the natural appearance of the illuminated objects. Thanks to the IP20 degree of protection and modern design, the setting perfectly fits into the minimalistic aesthetics of each arrangement.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 9 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	830
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED 2835
LED quantity	30
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	90-110
Height	26 mm
Fixture's diameter	120 mm
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200753


EAN: 5905378200753

**DOWNLIGHT MOLLY 3000K 9W 830lm
round IP20 White LITE**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	124 mm
Height	37 mm
Length	123 mm
Weight	0,11 kg

Bulk packaging

Quantity	100
Width	390 mm
Height	266 mm
Length	640 mm
Volume	0,043 m3
Weight	12,1 kg

Europallet

Quantity	2800
Height	1,9 m
Quantity in layer	400
Number of layers	7
Bulk quantity	28
Weight	369 kg

LED line LITE

Code: 200753

EAN: 5905378200753

**DOWNLIGHT MOLLY 3000K 9W 830lm
round IP20 White LITE**

Example application

