

LED line PRIME

Code: 201330-DALI

EAN: 5905378220010

Panel Backlit 40W 4000K 4800lm
120x30 DALI PRIME



LED line PRIME Panel Backlit 40W is an advanced 40W lighting solution emitting a white light with a temperature of 4000K and a light stream of 4800 lm. It has a light angle of 120°, which ensures optimal light scattering. Made of aluminium and polystyrene, it is characterized by high quality and durability up to 75,000 hours of operation. It offers Ra color reproduction factor of 80 and D energy efficiency class.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤3
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0.9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 201330-DALI

EAN: 5905378220010

**Panel Backlit 40W 4000K 4800lm
120x30 DALI PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 201330-DALI

EAN: 5905378220010

**Panel Backlit 40W 4000K 4800lm
120x30 DALI PRIME**

Example application