


LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Voltage range and voltage type



Ambient temperature suitable for operation



Lifespan



Dimmable



Manufacturer issues a 5-year warranty for this product.



Beam angle




LED type




LED quantity (1m)

Parameter	Value
Colour of the light	Green
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (1m)	2,4 W
Current (1m)	0,2
Supply voltage range and voltage type	12 DC
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2


Parameter	Value
LED quantity (1m)	30
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	` -20 ÷ 45 °C
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Product weight with packaging (g)	103 g
Master carton weight (kg)	7,73



Single packaging



Bulk packaging



Europallet

