

LED line LITE

product_card.label_product_code: 200852
product_card.label_product_gtin: 5905378200852

Downlight MOLLY 12W 1150lm 3000K square



product_card.label_technical_data

product_card.label_attribute_name	product_card.label_attribute_value
Luminous efficacy	95 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1150 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Weight	132.2 g
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	120-135
The lumen maintenance factor	96 %
Material (housing)	Polycarbonate
LED type	SMD LED 2835

product_card.label_attribute_name	product_card.label_attribute_value
LED quantity	56
Lifespan	30000 h
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
Mounting hole diameter	60 mm
For indoor use	Inside
IEC protection class	II
Length	145 mm
Width	145 mm
Height	26 mm
Power	• 12 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K

LED line LITE


product_card.label_product_code: 200852
product_card.label_product_gtin: 5905378200852

Downlight MOLLY 12W 1150lm 3000K square




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



product_card.label_single_package

Width	151
Height	36 mm
Length	151 mm
Weight	0,17 kg

product_card.label_collective_package

Number of pieces/tape in meters pack zb	60
Width	473 mm
Height of collective packaging	322
Length	390 mm
Weight	11,1 kg
Volume	0,05939934 m3

product_card.label_europalette

LED line LITE

product_card.label.product_codeproduct_card.label.product_gtin:
2008525905378200852

Downlight MOLLY 12W 1150lm 3000K
square

product_card.label.realization_photo



zdjęcie-realizacji.png