

LED line PRIME

Code: 479969

EAN: 5907777479969

LED line PRIME LED strip 192 SMD 24V
2700K 17,5W 160lm/W



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	160 lm/W	LED type	SMD
Colour of the light	White	LED quantity	960
Energy efficiency class 2019/2015	D	Compatible dimmer type	PWM
Colour consistency in MacAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	3
Warranty (years)	5	LED quantity (lm)	192
Dimmable function	PWM	Type of adhesive tape	3M 300 LSE
Survival factor	0.9	Colour consistency in MacAdam ellipses	≤3
Minimum purchase quantity	5	Ambient temperature suitable for operation	-25÷45 °C
Lifetime L70B50	50 000	For indoor use	Inside
Wire length	200 mm	IEC protection class	III
Wattage (lm)	17,5 W	Length	5000 mm
Luminous flux (lm)	2800	Width	10 mm
Current (lm)	0,73	Height	2,5 mm
Colour rendering index Ra	80	Power	• 17.5
Metres per roll	5	Voltage	• 24 V DC
The lumen maintenance factor	96 %	Correlated colour temperature	• 2700 K
Beam angle	120 °		

LED line PRIME

Code: 479969

EAN: 5907777479969


LED line PRIME LED strip 192 SMD 24V
2700K 17,5W 160lm/W

Dimensions


Light distribution

Additional product photos

Additional product photos




Logistics data




Single packaging

Width	153 mm
Height	15 mm mm
Length	153 mm mm
Weight	0,15 kg
	5



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm mm
Height of collective packaging	180 mm
Length	320 mm mm
Weight	6,34 kg kg
Volume	0,020 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	405,4 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 479969

EAN: 5907777479969

**LED line PRIME LED strip 192 SMD 24V
2700K 17,5W 160lm/W**

Example application