

LED line PRIME

Code: 201613

EAN: 5905378201613

LED line PRIME LED bulb E14 5W 4000K
700lm 170-250V C37



Technical data

Parameter	Value
Luminous efficacy	140 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	700 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Lamp's type	C37
Lamp's diameter	37

Parameter	Value
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Power	• 5 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 201613

EAN: 5905378201613

LED line PRIME LED bulb E14 5W 4000K
700lm 170-250V C37


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	50 mm
Height	105 mm mm
Length	50 mm mm
Weight	0,06 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	500 mm mm
Height of collective packaging	270 mm
Length	255 mm mm
Weight	7 kg kg
Volume	0,034 m3 m3



Europallet

Quantity collective euro pallet	4200 szt.
Weight of a euro pallet	294 kg
Pallet height	1890 mm
Quantity in 1 layer	600 szt.
Number of layers	7

LED line PRIME

Code: 201613

EAN: 5905378201613

**LED line PRIME LED bulb E14 5W 4000K
700lm 170-250V C37**

Example application