

LED line PRIME

Code: 217539

EAN: 5905378217539


**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**



SUNLO is an innovative solar luminaire that combines elegant, **modern** design with advanced technology. Thanks to the use of an A-class monocrystalline solar panel, it ensures the highest solar energy conversion efficiency.

The **SUNLO** luminaire offers two operating **modes: full power 100%** (lighting from dusk to dawn) and **eco mode 50%**, which extends operating time and reduces energy consumption.

Additionally, it allows adjustment of the color temperature in the range of **3000 K** (warm) or **4000 K** (neutral). This allows for precise adaptation of the lighting character to the surroundings and individual user preferences.



Technical data

Parameter	Value
Warranty	5
Power	• 20 W
Correlated colour temperature	• 3000 K • 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IEC protection class	III
Luminous flux	2200
Lifetime L70B50	35 000 h
Loading time	6 h
Mounting type	Lighting pole ø 60mm
Type of battery	LiFe PO4 6.4V 6000 mAh

Parameter	Value
Beam angle	120
Motion detection range and angle	120
LED type	SMD 2835
LED quantity	64
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20 +50
For indoor use	Outside
Height	120 mm
Fixture's diameter	400 mm
Colour	black
Material (housing)	ABS
Material (cover)	Polycarbonate

LED line PRIME

Code: 217539

EAN: 5905378217539

**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	150 mm
Height	430 mm
Length	430 mm
Weight	3,4 kg

Bulk packaging

Quantity	1
----------	---

Europallet

Quantity	48
Quantity in layer	
Number of layers	
Bulk quantity	48
Weight	200 kg

LED line PRIME

Code: 217539

EAN: 5905378217539

**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**

Example application

